

ABN 5700 664 9743

ACN 006 649 743

## Write 'n' Wipe Wallcovering by Nemor

Write n wipe is a high-performance wallcovering which provides a dry-erase writing surface that adds function and visual clarity to offices, conference rooms, training rooms, classrooms, and children's rooms. This strong and durable wallcovering transforms any wall or smooth surface into a continuous dry-erase writing area that is highly legible and will withstand the rigorous use required for classrooms and offices.









Fax +61 (3) 9335 6788

Phone +61 (3) 9335 6711 Unit 2/5 Ovata Drive Tullamarine Vic. 3043

enquiries@humeinternationale.com www.humeinternationale.com

ABN 5700 664 9743

ACN 006 649 743

## **Technical information**

Total weight: 400gsm

Substrate type: Non woven fabric backing Roll Size: 126cm x 30m - cut lengths available

Adhesive: Hume - Dynamite 7760 Vinyl over Vinyl [VOV]

Stain / Chemical resistance: Excellent resistance to temporary staining of most staining agents and chemicals

Microbiological Resistance: Manufactured to have a high degree of microbiological resistance by incorporating an active bio-stabiliser.

Mildew: Will also prohibit the growth of fungi and mildew on the surface of the wallcovering. Demonstrates excellent resistance to the pink staining organism Stv. Reticlum and will exhibit no growth of a mixed fungal spore, suspension of:

- Aspergillus niger
- Chaetomium globosum
- Giocladium vierns
- Penicilium pinophilium
- Aureibasidium pullulans

Bacteria: Demonstrates excellent resistance to the Gram positive bacteria Staphlococcus aureus, Methycillinresistant staphylococcus aureus (MRSA) and the Gram-negative Kiebsiella pneumoniae

**Light Fastness:** Excellent (7 out of 8 to BSEN ISO 105-B02)

Hanging Instructions: Due care must be taken to ensure the wall surface is adequately prepared – it should be sound, free from dust, equal in colour and mirror smooth. This product can be hung either vertically or horizontally depending on the area being covered. Every other stips should be hung reversed to the previous regardless of vertical or horizontal installation. The joints should be overlapped by approximately 3cm then double cut. For best results use a spatula to smooth the joints, remove air bubbles and creases. Use a straight edge and sharp trimming knife at joints and corenrs. Do not puncture the air bubbles and do not use metal or sharp objects on the surface of the wallcovering, other than when cutting in. Only use in conjunction with dry erase pens. Clena the surface using a micro fibre cloth after each use. Do not use permanent markers or cleam with any abrasive products.

Maintenance: Fully washable and in most cases, dirt and stains can be removed using a suitable cleaning agent or even solvents including chlorine based cleaning agents. Abrasive cleaning agents or brushes should be avoided as this may damage the integrity of the write n' wipe finish

1.	Distill	ed '	Water,	cold

2. Distilled water, hot

Ethly Alcohol(50% by volume)

4. Vinegar Solution (3% acetic acid)

Alkali solution (1% sodium hydroxide) 5.

6. Acid solution (5% acetic or hydrochloric acid)

7. Soap solution

8. Detergent solution

9. Pure Orange Juice

10. Butter

11. Catsup

12. Tea





Fax +61 (3) 9335 6788

Phone +61 (3) 9335 6711 Unit 2/5 Ouata Drive

enquiries@humeinternationale.com Tullamarine Vic. 3043 www.humeinternationale.com

ABN 5700 664 9743

ACN 006 649 743

Quality Assurance: Manufactured to ISO9001:2008

## Fire standards:

- Australian BCA Group Classification 1 when tested in accordance with AS/NZS 3837:1998 (AWTA Product Testing Laboratory - 28/10/2009). These are the most current Australian fire rating
- Class 'O' inaccordance with the British Building Regulations. (Class 1 to BS476: Part 7) and Euroclass B in accordance with EN 13501-1:2007+A1:2009

## What is the commercial product warranty?

The manufacturer warrants that for a period of 5 years from the installation of its commercial wallcoverings, they shall not separate from their backings or support the growth of mildew when wallcoverings are installed properly onto a sound surface, adequately maintained and used under normal conditions.

The warranty is not assignable and extends only to the purchasers who are the owners of wallcoverings at the time of installation.

The manufacturer will supply replacement wallcoverings free of charge if any of its wallcoverings fail to conform to this warranty.

