

## TECHNICAL INFORMATION

**Physical properties**

Total weight: 540 /m<sup>2</sup> (nominal)  
 Vinyl Weight: 480 /m<sup>2</sup> (nominal)  
 Substrate Type: Polycotton Osnaburg  
 Fabric Backing  
 Substrate weight: 60g/m<sup>2</sup> (nominal)

**Roll size:**

137cm x 27.4m - cut lengths available

**Fire Rating:**

Class 0&1 to BS 476 parts 6 & 7.  
 Euroclass B - s2, d0 as minimum.  
 Suitable for all areas of commercial buildings.

**Adhesive:**

Fabric backed vinyls - Newmor Heavy.  
 Varies with substrate - please enquire.

**Bacteria Resistance:**

Contains an active Fungicide.

**Light Fast:**

Excellent Light Fastness  
 BS EN ISO 105-B02 7/8

LRV = Light reflective value

**Specifications**

Conforms to requirements of BS EN 15102,  
 BS EN 259 and WA - Quality Standard W-101

**Stain/Chemical Resistance:**

Pass ASTM D-1308-1987 Federal Spot Test.  
 Resistant to temporary staining of oils,  
 fats, mild acids and alkalis.

**Quality Assurance:**

Our management systems and production  
 procedures comply with ISO 9001, the  
 internationally recognised Quality  
 Standard.

**Availability:**

Every product stocked in depth.  
 Please allow 5/7 days for delivery.

**Warranty:**

Newmor offers a five year warranty  
 against manufacturing defects.  
 Full details available on application.

**Samples:**

Larger samples are readily available on  
 request.

**Maintenance:**

Fully washable and in most cases products  
 can be scrubbed repeatedly to remove any  
 marks without damaging the product itself.  
 Most products are also able to withstand  
 the use of chlorine releasing agent solutions.



FM 23833



British Product | Global Support



**Newmor**  
 WALLCOVERINGS

**UK SALES:**

T: 01938 551990

E: sales@newmor.com

**EXPORT SALES:**

T: + 44 (0) 1938 55 2671

E: enquires@newmor.com